

AVAILABLE WITH LED LAMP HEADS



# QUICK™ UQLXN-2MR COMBINATION SERIES

Thermoplastic LED Combination Units



TYPE \_\_\_\_\_

CATALOG # \_\_\_\_\_

NOTES \_\_\_\_\_

## FEATURES

### Construction

- Frame, faceplate, backplate and canopy are made of Thermoplastic
- 6 inch EXIT lettering legend, available in Red or Green

### Mounting

- Surface Mount
- Universal model includes (2) faceplates, (1) backplate and (1) canopy
- Canopy included for end or ceiling mount applications
- Backplate features universal knockouts for a standard 4 inch junction box used in wall mount applications

### Finishes

- Finished in mist-white

### Chevrons

- Faceplate includes two field-selectable, snap-in/out chevron indicators

### Exit Legend LEDs

- Red or Green Long-Life Light Emitting Diodes (LED) illumination

### Combination Units

- Lead-Calcium battery models offer a choice of 6V-12W total battery capacity

### Lamp Head Source

- Choice of MR16 6V-5W
- Choice of MR16 LED 6V-4W, with life expectancy 50,000+ hours
- Lamp heads are fully adjustable with no tools required.

### Self-Diagnostics

- Not Available

### Special Wording Panels

- Not Available

### Approvals

- Listed to UL 924 Standards
- UL listed for Damp location (50°F to 104°F, 10°C to 40°C)
- Meets NFPA101 (Life Safety Code), NFPA 70 NEC, OSHA illumination standards

### Warranty

- Three-Year full warranty (subject to proper installation and maintenance)

## ACCESSORIES

(Order as a separate item)

Wire Guard (Wall mount)	WG6-L
-------------------------	-------

## POWER CONSUMPTION CHART

120/277VAC, 60Hz 0.11/0.05A
-----------------------------

## ORDERING FORMAT

SERIES	LEGEND COLOR	LAMP TYPE
UQLXN500	R= Red G= Green	-2MRSN= 6V-5W Halogen MR16 -2LD1N= 6V-4W LED MR16

EXAMPLE: UQLXN500R-2MRSN

## SPECIFICATIONS

Supply and Install Lightalarms® Quick™ UQLXN-2MR Combination Series. The Combination Unit specified includes (2) faceplates, (1) backplate and (1) canopy. The frame, faceplate, backplate and canopy shall be constructed of injection-molded Thermoplastic. Frame, backplate and canopy shall be mist-white. Faceplate shall be mist-white with a (R) red or (G) green legend. Snap together design allows for no screws being necessary to hold the faceplate(s) or backplate together. The faceplate shall come standard with two field-selectable, removable snap-in/out chevron indicators. The combination model shall be suitable for surface mount, end wall or ceiling installations.

The EXIT illumination source shall be Light Emitting Diodes (LED) in (R) red or (G) green color. The LEDs shall provide illumination in normal and emergency operation mode. The LEDs shall be mounted inside the Exit Sign housing. A color matching LED sensitive legend diffuser of (R) red or (G) green, shall be mounted in front of the LEDs to provide the 6" high by 3/4" stroke EXIT letters with even illumination and no visible LEDs or hot spots.

Combination Units shall be equipped with two MR16 type emergency heads with either MR16 6V-5W halogen or 6V-4W LED as specified. Emergency heads are adjustable and can be aimed with no tools required.

Combination Units shall be 120/277VAC, 60Hz, with power consumption of .1/0.05A and supplied with a sealed maintenance-free Lead-Calcium battery, providing at least 90 minutes, illumination upon AC failure.

The Combination Units sbe tested by Underwriters Laboratories, listed to UL 924 standards, and UL listed for Damp location (50°F to 104°F, 10°C to 40°C). The Combination Units shall meet NFPA101 (Life Safety Code), NFPA 70-NEC and OSHA illumination standards. Includes a three-year full warranty.

The combination unit shall be Lightalarms® Model \_\_\_\_\_.

## DIMENSIONS

Dimensions are approximate and subject to change.

