



GALAXY™ SLIM TX & TXE SERIES

Die-Cast aluminum slim profile Exit Sign
with long-lasting LED performance



TYPE _____

CATALOG # _____

NOTES _____

FEATURES

Construction

- Faceplate, backplate and canopy are made of die-cast aluminum
- 6 inch EXIT lettering legend, available in Red or Green

Mounting

- Surface Mount
- Single face model includes (1) faceplate, (1) back-plate and (1) canopy
- Double face model includes (2) faceplates and (1) canopy
- Canopy included for end or ceiling mount applications
- Backplate features universal knockouts for a standard 4 inch junction box, used in wall mount applications

Finishes

- Choice of finishes: all white, or black with brushed aluminum faceplate
- Clear lacquer finish inhibits fingerprints and other contaminants

Chevrons

- Faceplate includes two field-selectable, knock-out chevron indicators

LEDs

- Red or Green Long-Life Light Emitting Diodes (LED) illumination

Self-Diagnostics

- Not Available

Special Wording Panels

- Not Available

Approvals

- Listed to UL 924 Standards for Damp location (32°F to 122°F, 0°C to 50°C)
- Meets NFPA101 (Life Safety Code), NFPA 70 NEC, OSHA illumination standards

Warranty

- Five-Year full warranty (subject to proper installation and maintenance)

ACCESSORIES

(Order as a separate item)

Wire Guard (Wall Mount)	WG1-L
Wire Guard (Ceiling Mount and End Mount)	WG5-L

POWER CONSUMPTION CHART

MODEL	AC SPECS			DC SPECS	
	120/277VAC, 60Hz	Typical 1W	Less than 1.5W	–	–
AC-Only	120/277VAC, 60Hz	Typical 1W	Less than 1.5W	–	–
Self-Powered	120/277VAC, 60Hz	Less than 3.3W	Less than 1.5W	Ni-Cd battery	Min. 90 minutes

ORDERING FORMAT

NO. OF FACE	SERIES	BACKPLATE COLOR	LEGEND COLOR	FACEPLATE COLOR
Blank = Single Face 2 = Double Face	TX = AC-Only TXE = Self-Powered	W = White B = Black	R = Red G = Green	W = White (only available with white backplate) A = Brushed Aluminium (only available with black backplate)

EXAMPLE: TXEWRW

SPECIFICATIONS

Supply and Install Lightalarms® Galaxy™ Slim TX, TXE Series.

The Exit Sign specified as single face shall be standard with (1) faceplate, (1) backplate and (1) canopy and specified as double face shall be standard with (2) faceplates and (1) canopy.

The faceplate, backplate and canopy shall be constructed of die-cast aluminum. Backplate and canopy shall be matching in color, (W) white or (B) black. Faceplate shall be (W) white (with a white backplate) or (A) brushed aluminum (with a black backplate) covered with a clear lacquer finish.

Snap together design, allows for no screws being necessary to hold the faceplate(s) or backplate together. The faceplate shall come standard with two field-selectable, removable knockout chevron indicators. The single face Exit Sign shall be suitable for surface mount, wall, end or ceiling installations. The double face Exit Sign shall be suitable for surface mount, end or ceiling installations.

The illumination source shall be Light Emitting Diodes (LED) in (R) red or (G) green color. The LEDs shall provide illumination in normal and emergency operation mode. The LEDs shall be mounted inside the Exit Sign housing. A color matching LED sensitive legend diffuser of (R) red or (G) green, shall be mounted in front of the LEDs to provide the 6" high by ¾" stroke EXIT letters with even illumination and no visible LEDs or hot spots.

AC-Only models shall be 120/277VAC, 60Hz, with a maximum power consumption of 1.5W.

Self-Powered models shall be 120/277VAC, 60Hz, maximum 1.5W and supplied with a sealed maintenance-free Nickel-Cadmium battery, providing at least 90 minutes illumination upon AC failure.

The Exit Sign shall be tested by Underwriters Laboratories, listed to UL 924 standards, and UL listed for Damp location (32°F to 122°F, 0°C to 50°C) and meets NFPA101 (Life Safety Code), NFPA 70-NEC and OSHA illumination standards. Includes a five-year full warranty.

The Exit Sign shall be Lightalarms® Model _____.

DIMENSIONS

Dimensions are approximate and subject to change.

