

1000W Capacity Mini Inverter Series

Interruptible unit equipment standard with non-audible improved self-diagnostics circuitry



Housing

- 14-Gauge Steel
- White semi-gloss powder-coat paint finish

Mounting

- Surface mount

Compatible loads:

- LED
- Incandescent
- Fluorescent
- Operating switched, normally-on or normally-off fixture types
- 0-10V dimming
- Triac dimming
- DALI dimming - consult factory

Load capacity

- 1000W
- Line voltage allows for remote mounting of the emergency fixtures at distances up to 1000 feet

Electronics

- High-efficiency pure sine wave inverter
- Temperature compensated charger
- Replaceable output fuse protection
- Low battery voltage disconnect
- Unit comes standard with electronic lockout and brownout circuits

Controls

- Standard with a non-audible self diagnostic/charger is fully self-contained, fully automatic microcontroller-based system
- Optional audible auto diagnostic available
- Optional no Advanced Diagnostics available
- No Advanced Diagnostics option must be selected in conjunction with transfer switches
- Standard lighting control override for 0-10V dimming systems
- Optional 4 output circuits allow for multiple switch compatibility

Sealed maintenance-free battery

- 12V valve regulated Lead-Calcium (VRLA) batteries
- Provides 90 minutes of emergency operation power requirements
- Choice of Voltage 120V input/120V output or 277V input/277V output operation, 60Hz

Approvals

- UL924 Standard
- Meets or exceeds all National Electric Code and Life Safety Code Emergency Lighting Requirements

Warranty (subject to proper installation and maintenance)

Unit has a three-year limited warranty

Detailed warranty terms located on [page 182](#) or online at: www.lightalarms.com



Replacement battery

Series	Part number
LMIU-1000	4 X 860.0043

Specifications

Transfer time	Voltage regulation on emergency	Frequency regulation on emergency	Load power factor range	Operating temperature
Less than 1 second	+/- 3%	60 Hz +/- 1%	0.8 at 120V 1 at 277V	68°F to 86°F (20° to 30°C)

Electrical characteristics and dimensions

Power rating	Sine wave	Installation	Cabinet dimensions			Number of batteries	Weight	Weight w/o battery
			W"	H"	D"		120V & 277V	120V & 277V
1000W	Pure	Floor/ Wall	24"	40.75"	10.5"	4	266 lbs	114 lbs
1000W-4C	Pure	Floor/ Wall	24"	40.75"	14.5"	4	320 lbs	198 lbs

Note: For wiring diagram, please refer to the specification sheets

Power consumption and unit rating

Model number	Ac specs	Emergency power available for load			
		90 minutes	2H	3H	4H
LMIU-1000	120 / 277VAC 12.8 / 5.3 Amps	1000W	807W	604W	489W

Ordering format

Series	Capacity	Voltage in/out	Diagnostic feature	Options
LMIU	-1000=1000W	Blank= 120/120VAC or 277/277VAC	Blank= Includes improved self-diagnostics (non-audible) ¹ -ID= Improved self-diagnostics (audible) ¹ -NID= No self-test/Self-diagnostic -NEX= Nexus® wired -NEXRF= Nexus® wireless	-D3= Time delay (15 minutes) -SAC= Service alarm contact ² -4C= 4 output circuits

Example: LMIU-1000

¹ Minimum load required: 10% of unit capacity

² Service alarm contact (SAC) shall be provided a 24V signal, the charger board will indicate a fault by closing a contact.