

Grande™ Exit Series

Specification-grade, LED, thermoplastic, snap together exit sign



Grande™ Thermoplastic Family



Grande™
Combo series
PG. 38-39



Grande™ Compact
Battery series
PG. 88-89



Grande™
Battery series
PG. 90-91



ELF640 &
ELF650
Remote series
PG. 136-137

Construction

- Mist white or black UV stabilized thermoplastic enclosure
- 6 inch EXIT lettering legend, available in red or green
- Field-selectable chevrons

Mounting

- Surface mount
- Canopy included for end or ceiling mount applications
- Universal J-Box mounting

Special Wording Panels

Available. Contact your sales representative with your design requirements

Electronics

- Optional Improved Diagnostics
- Optional Nexus®Pro IoT monitoring system
- Optional Nexus® wireless monitoring system
- 120/277 60Hz
- Compatible with Lightalarms Mini Inverters (contact your sales representative for more information)

Approvals

- UL 924 Listed
- Damp location 32°F to 104°F (0°C to 40°C)
- Meets NFPA101 (Life Safety Code), NFPA 70 NEC, OSHA illumination standards
- E-California Energy Commission Title 20

Warranty (subject to proper installation and maintenance)

Five-year limited warranty

Detailed warranty terms located on **page 197** or online at: www.lightalarms.com

nexus

id.
improved
diagnostics




Nexus®Pro



Housing color




Black



White

Dimensions (Dimensions are approximate and subject to change):



Power consumption chart

| Model | AC Specs | DC Specs |
|------------------------------|-----------------------------------|-------------------------------------------|
| AC-Only | 120/277VAC, 60Hz (Less than 2.5W) | – |
| AC / DC-remote | 120/277VAC, 60Hz (Less than 2W) | 6 to 48VDC (Less than 1.5W) |
| Self-powered | 120/277VAC, 60Hz (Less than 3.3W) | Nickel-Cadmium battery (Min . 90 minutes) |
| Self-powered with Diagnostic | 120/277VAC, 60Hz (Less than 2.8W) | Nickel-Cadmium battery (Min . 90 minutes) |

Accessories (Order as a separate item)

| Description | Product Code |
|------------------------------------------|--------------|
| Wire guard, Back mount | WG1-L |
| Wire guard (ceiling mount and end mount) | WG5-L |
| Pendant white | GRA-P*-W |
| Pendant black | GRA-P*-B |

*Specify pendant length (12", 24", 36" etc)

Ordering format

| Series | Unit type | Legend color/ # of face | Housing color | Options |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GRAN | AC = AC-Only (120/277V) DC = 120/277VAC & 6 to 48VDC 21 = Dual AC circuit (2x120V) 22 = Dual AC circuit (2x277V) N = Self-powered Nickel-Cadmium ND = Self-powered with Improved Diagnostics circuitry -NEXP = Nexus®Pro IoT ¹ -NEXRF = Nexus® wireless ¹ | R = Red universal G = Green universal R1 = Red single face ³ R2 = Red double face ³ G1 = Green single face ³ G2 = Green double face ³ Open face ² RW = Red on white universal GW = Green on white universal Universal = (2) faceplates, (1) backplate and (1) canopy Single face = (1) faceplate, (1) backplate and (1) canopy Double face = (2) faceplates and (1) canopy | W = White B = Black | BA = Brushed aluminum exit stencil -FAF = Fire alarm activated flasher (AC, DC, 21,22 or ND models only) -FB = Flasher buzzer (ND model only) -FBF = Flasher Buzzer + Fire alarm activated flasher (ND model only) -FL = Flasher (ND model only) -LVR1 = Polycarbonate shield with tamper proof screws -VR = Vandal-resistant screws |

Example: GRANACRW

¹ Consult your sales representative

² Open face required with special wording legends

³ Specify single or double for LVR1 or VR options only