

## Nexus® RF

### Area Controller Router V2



#### Features

- Stores back up of Nexus® RF database containing all system and unit information
- Coordinates up to 100 nodes
- SD micro flash memory 16GB
- Communicates to units via 918 - 925.8 MHz mesh network
- Ethernet port for LAN connectivity
- 50 ohm SMA antenna jack
- Mains plug pack 100-240VAC, 12VDC 2A max output
- Suitable for indoor application
- 10°C - 40°C ambient temperature

#### Includes

- 2m blue Cat 5e UTP patch lead
- Wall bracket
- 75mm stub antenna
- Optional protective cover

#### Warranty

- Five Year warranty

See warranty details at: [www.lightalarms.com](http://www.lightalarms.com)

## nexus®

#### Power consumption

Catalogue No.	Power consumption
NEXUS-ACRN-LA	3W

#### Power requirements

Catalogue No.	Power requirements
NEXUS-ACRN-LA	100-240VAC

#### Ordering information

Catalog No.	Description
NEXUS-ACRN-LA	Nexus® RF Area Controller Router

#### Dimensions

Length	Width	Height
243mm	62mm	150mm

#### Weight

Catalogue No.	Weight
NEXUS-ACRN-LA	1.0Kg

#### Construction

Part	Construction
Body	Polycarbonate
Bracket	Zinc Steel
Body	Polyurethane