

SMA Series

Surface-mount architectural battery unit



BATTERY UNITS

Standard features

- Easy to install on the ceiling surface or pendant-mount (pendant kit sold separately)
- Thermoplastic decorative housing, white finish or optional black
- High-temperature rated lithium battery with protection control module
- Infrared remote test control
- Two-wire universal AC input: 120-277VAC 50/60Hz
- Minimum 90 minutes of emergency lighting
- Battery full recharge in 24 hours
- Fixed, optimized light distribution for ceiling heights up to 12 ft
- Four high-intensity LED with redundant connections; 140 lm/W
- Listed UL924 for damp locations: 50° to 104°F
- BC - California Energy Commission Title 20
- Warranty details at: www.lightalarms.com

Optional features

- Time delay: 15 minutes
- Self-test and diagnostics
- Nexus®Pro: Bluetooth® central monitoring system
- Fixed, square light distribution for area of rescue, up to 12-ft ceilings




Remote test control

Photometric performance

The **SMA Series** has a fixed lighting distribution, optimized by design for ceiling heights up to 12 ft. Unlike equipment with adjustable lights, the **SMA Series** makes the installation faster and prevents errors leading to insufficient lighting on the path of egress.

The **SMA Series** delivers a stable and consistent illumination making it easy to specify in a wide range of applications. The spacing of illumination ranges from 62 to 80 feet for standard units (corridor). The area-of-rescue option covers a square surface up to 729 ft² (27 ft x 27 ft).




Spacing: standard unit – 6 ft wide corridor

Mounting height	Spacing center-to-center	Single unit coverage
8 ft	62 ft	57 ft
10 ft	80 ft	77 ft
12 ft	72 ft	69 ft

Nexus®Pro   

Dimensions (Dimensions are approximate and subject to change)



Ordering format

Series	Color	Unit type	Options
SMA = Surface mount architectural	W = Factory white B = Black	Blank = Standard charger D = Advanced diagnostics, non-audible NEXP = Nexus®Pro wireless Bluetooth®	Blank = No options D3 = 15 minute time delay SQ = Square lighting pattern

Example: SMAWDSQ

NOTE: Pendant mount compatible.
Pendant kit sold separately.