



Die Cast Aluminum LED AC, AC/DC, or Self-Powered Exit Signs





New Compact Design and Diagnostic/Self-Test Feature



Dimensions are approximate and subject to change.

	A	B
6" letters	8 ⁴ / ₅ "	13 ¹ / ₁₆ "
8" letters	10 ¹ / ₂ "	15 ¹ / ₄ "



NRTL. UL 924

features

- Precision die cast aluminum housing features invisible, universal chevron and mounting knockouts.
- Optional damp location listing on all models.
- High intensity LED's with diffuser disperses light and enhances brightness for a fully even illuminated 3/4" stroke.
- LED's draw only 2 watts of electricity for either single or double face signs.
- Low profile mounting canopy included with all exit signs for universal top, end or back mount.
- All AC only signs come wired as AC/DC signs which operate off a remote DC power source when AC power fails. DC input is a 2-wire, 6-48VDC universal input.

self-powered units

- Self-Powered Models are self contained, all circuitry and batteries are contained inside the exit housing.
- Fully integrated circuitry includes a 2-wire 120-347AC voltage input transformer, automatic, temperature compensated charger, charge monitor LED and test switch.
- Long life, maintenance-free, sealed nickel cadmium battery
- **Diagnostic / Self Test Standard:** Continuously monitor every critical function of the unit. Unit automatically performs monthly testing in accordance with NFPA101, Life Safety Code.

diagnostic / self test feature (standard)

The diagnostic/self test feature continuously monitors the charger assembly, battery and LED assembly current. If a fault is indicated the external service required indicator will illuminate. The internal fault indicators will then indicate the nature of the fault. The diagnostic/self test will self test for 30 seconds every 30 days, 30 minutes every 60 days and 90 minutes annually. Meets NFPA 101 Life Safety Code requirements for periodic testing.

options

(Add Prefix to Model No.)

8" EXIT legend for NYC code **Prefix -8**

(Add Suffix to Model No.)

Dual Circuit (AC only) **Suffix -2**
 Open Face / Special Wording **-Y**
 Vandal Resistant Screws **-VR**
 Lexan Face Shield with Vandal Resistant Screws **-LVR**
 Fire Alarm Activated Flasher (Self-powered signs only) **-FAF**
 Buzzer and Flasher (Self-powered signs only) **-FB**
 Damp location listing **-DL**
 Custom Color and Finishes available upon request.

accessories

(Order as separate item)

12" Pendant Mount White **Model GPW**
 12" Pendant Mount Black **GPB**

*Custom pendant length and colors available, contact factory.

ordering format

GXE **B** **R** **A** **-VR** **-N**
 | | | | | |
 Series Unit Color Letter Color Stencil Color Option Standard
 Single Face Black Red Brushed Vandal Resistant Series
 Self-Powered Exit Aluminum Screws Designator

selection chart

Series		Unit Colors		Letter Colors		Face Colors	
Description	Symbol	Descr.	Symb.	Descr.	Symb.	Descr.	Symb.
AC-Only Single Face	GX □	Black	B □	Red	R □	Black	B □
	2GX □	White	W □		Green	G □	White
Self-Powered Single Face	GXE □	Brushed Aluminum	A □	Green	G □	Brushed Aluminum	A □
	2GXE □						